



- 記事**
1. グレーチング: SUS304
 2. 受枠: スチール(溶融亜鉛メッキ)
 3. 目地: SUS304

適用	溝幅	適応荷重	セット型式	グレーチング型式	受枠型式	L1	L2	L3	L4	L5	GR嵩上げ材本数	補強材/本数
	150	歩道用	RS-CBC015	RS-CBC15G	RS-CBC015W	210	200	57	-	30	3	-
	180		RS-CBC018	RS-CBC18G	RS-CBC018W	250	240	77	-	35	3	-
	240		RS-CBC024	RS-CBC24G	RS-CBC024W	330	320	117	-	45	3	-
	300		RS-CBC030	RS-CBC30G	RS-CBC030W	400	390	152	-	50	3	-
	150	T-2	RS-CBC215	RS-CBC15G	RS-CBC215W	210	200	57	-	30	3	-
	180		RS-CBC218	RS-CBC18G	RS-CBC218W	250	240	77	-	35	3	-
	240		RS-CBC224	RS-CBC24G	RS-CBC224W	330	320	117	200	45	3	□20x40x2.3/3
	300		RS-CBC230	RS-CBC30G	RS-CBC230W	400	390	152	260	50	3	□20x40x2.3/3

APPROVED BY		掃除口用ガラガラスリムレインシューター Bタイプ(センタースリット)	WORK NO.	
JUDGED BY			DRAWING NO.	NSG-1435115-2
ENG'R IN CHARGE				
CHECKED BY				
DATE DRAWN				
SCALE	1/6			

DAIKURE CO., LTD.

計	
控	
製	
作	
管	
理	
見	
積	
決	
定	
図	
申	
請	
配	
布	
部	
数	
製	
作	
見	
積	
決	
定	
図	
返	
却	
申	
請	
日	
付	

営業所図番