



適用	溝幅	適応荷重	セット型式	グレーチング型式	受枠型式	L1	L2	L3	L4	L5	GR嵩上げ材本数	補強材/本数
	150	歩道用	RS-CBS015	RS-CBS15G	RS-CBS015W	210	200	120	-	30	3	-
	180		RS-CBS018	RS-CBS18G	RS-CBS018W	250	240	160	-	35	3	-
	240		RS-CBS024	RS-CBS24G	RS-CBS024W	330	320	240	-	45	3	-
	300		RS-CBS030	RS-CBS30G	RS-CBS030W	400	390	310	-	50	3	-
	150	T-2	RS-CBS215	RS-CBS15G	RS-CBS215W	210	200	120	-	30	3	-
	180		RS-CBS218	RS-CBS18G	RS-CBS218W	250	240	160	-	35	3	-
	240		RS-CBS224	RS-CBS24G	RS-CBS224W	330	320	240	200	45	3	□20×40×2.3/3
	300		RS-CBS230	RS-CBS30G	RS-CBS230W	400	390	310	260	50	3	□20×40×2.3/3

APPROVED BY		WORK NO.	
JUDGED BY		DRAWING NO.	
ENG' R IN CHARGE		NSG-1435127-2	
CHECKED BY			
DRAWN BY			
DATE DRAWN			
SCALE	1/6		
DAIKURE CO., LTD.			

営業所図番

計	
控	
製	
作	
管	
理	
見	
積	
決	
定	
図	
申	
請	
配	
布	
部	
数	
製	
作	
見	
積	
決	
定	
図	
返	
却	
申	
請	
日	
付	