



記事

1. ビュート : スチール(溶融亜鉛メッキ)
2. 受 枠 : スチール(溶融亜鉛メッキ)

適用	榫穴口	適応荷重	セット型式	ビュート型式	受枠型式	L1	L2	L3	L4	L5	H	嵩上げ材	補強材	嵩上げ材本数
	□300		RS-DAS030S	RS-DAS030SG	RS-DAS030SW	400	390	383.6	361.8	-	110	KP20×40×2.3	-	3本
	□450	歩道用	RS-DAS045S	RS-DAS045SG	RS-DAS045SW	550	540	533.6	511.8	-	110			
	□600		RS-DAS060S	RS-DAS060SG	RS-DAS060SW	700	690	683.6	661.8	-	110			
	□300		RS-DAS230S	RS-DAS230SG	RS-DAS230SW	400	390	383.6	361.8	230	110	KP20×40×2.3	KP20×40×2.3	3本
	□450	T-2	RS-DAS245S	RS-DAS245SG	RS-DAS245SW	550	540	533.6	511.8	380	110			
	□600		RS-DAS260S	RS-DAS260SG	RS-DAS260SW	700	690	683.6	661.8	530	110			
	□300		RS-DAS430S	RS-DAS430SG	RS-DAS430SW	400	390	383.6	361.8	230	125	KP35×40×3.2	KP20×40×2.3	4本
	□450	T-14	RS-DAS445S	RS-DAS445SG	RS-DAS445SW	550	540	533.6	511.8	380	125			
	□600		RS-DAS460S	RS-DAS460SG	RS-DAS460SW	700	690	683.6	661.8	530	125			

APPROVED BY		スマートレインシューター 柵用	WORK NO.	
JUDGED BY			DRAWING NO. NSG-1835140	製作 見積 決定図 返却 申請図
ENG' R IN CHARGE				申請
CHECKED BY				配布部数
DRAWN BY		DATE DRAWN	日付	
SCALE	1/6	DAIKURE CO., LTD.		

営業所図番

計	
控	
製作	
管理	
見積	
決定図	
返却	
申請図	
日付	