



適用	側穴口	適応荷重	セット型式	グレーチング型式	受枠型式	L1	L2	L3	L4	L5	GR嵩上げ材本数	補強材/本数
	□300	歩道用	RS-DCS030	RS-DCS30G	RS-DCS030W	420	410	334	-	354	2	-
	□450		RS-DCS045	RS-DCS45G	RS-DCS045W	570	560	484	-	504	3	-
	□600		RS-DCS060	RS-DCS60G	RS-DCS060W	720	710	634	-	654	3	-
	□300	T-2	RS-DCS230	RS-DCS30G	RS-DCS230W	420	410	334	-	354	3	-
	□450		RS-DCS245	RS-DCS45G	RS-DCS245W	570	560	484	430	504	3	□20×40×2/1
	□600		RS-DCS260	RS-DCS60G	RS-DCS260W	720	710	634	580	654	4	□20×40×2/2

APPROVED BY		柵用ガラガラスリムレインシューター Cタイプ(サイドスリット)	WORK NO.	
JUDGED BY			DRAWING NO.	NSG-1435131-3
ENG' R IN CHARGE				
CHECKED BY				
DATE DRAWN				
SCALE	1/6			

DAIKURE CO., LTD.

営業所図番

計	
控	
製	
作	
管	
理	
見	
積	
決	
定	
図	
申	
請	
配	
布	
部	
数	
製	
作	
見	
積	
決	
定	
図	
返	
却	
申	
請	
日	
付	