



- 記事**
1. グレーチング : SUS304
 2. 受 枠 : スチール(溶融亜鉛メッキ)
 3. 目 地 : SUS304

適用	みぞ幅	適応荷重	セット型式	グレーチング型式	受枠型式	L1	L2	L3	L4	L5	補強アングル/本数
	150	T-14	RS-UBS415S	RS-UB4SG	RS-UBS415SW	210	174	130	40	30	L50×50×t6/5
	180		RS-UBS418S		RS-UBS418SW	250	214	160	45	35	L65×65×t6/5
	240		RS-UBS424S		RS-UBS424SW	330	294	220	55	45	L75×75×t6/5
	300		RS-UBS430S		RS-UBS430SW	400	364	280	60	50	L90×90×t6/5

APPROVED BY		スマートレインシューター U字溝用	WORK NO.	
JUDGED BY			DRAWING NO.	NSG-1835146-2
ENG' R IN CHARGE				
CHECKED BY				
DATE DRAWN		SCALE	1/6	
DAIKURE CO., LTD.		営業所図番		

計	
控	
製	
作	
管	
理	
見	
積	
決	
定	
図	
申	
請	
配	
布	
部	
数	
製	
作	
見	
積	
決	
定	
図	
返	
却	
申	
請	
図	
日	
付	