



ボルト固定部詳細

記事

1. 溝幅 : 300用 (13mmピッチ)
2. タイプ : FB3t, ザラザラタイプ
3. 材質 : SUS304

| グレーチング       |                 |             | 受 枠   |         | 荷重条件 |     |
|--------------|-----------------|-------------|-------|---------|------|-----|
| 型 式          | メインバー<br>高さ (h) | クロスバー<br>材料 | 型 式   | 寸法<br>H | 横断   | 側溝  |
| S3FRC35-1513 | 15              | FB3×10      | BB-15 | 18      | 人    | 人   |
| S3FRC35-2013 | 20              | FB3×10      | BB-20 | 23      | 人    | T2  |
| S3FRC35-2513 | 25              | FB3×15      | BB-25 | 28      | T2   | T2  |
| S3FRC35-3213 | 32              | FB3×15      | BB-32 | 35      | T6   | T14 |
| S3FRC35-3813 | 38              | FB3×20      | BB-38 | 41      | T14  | T20 |
| S3FRC35-4513 | 45              | FB3×20      | BB-45 | 48      | T20  | T20 |
| S3FRC35-5013 | 50              | FB3×20      | BB-50 | 53      | T20  | T20 |

|                  |  |             |
|------------------|--|-------------|
| APPROVED BY      |  | WORK NO.    |
| JUDGED BY        |  |             |
| ENG' R IN CHARGE |  |             |
| CHECKED BY       |  |             |
| DRAWN BY         |  |             |
| DATE DRAWN       |  | DRAWING NO. |
| SCALE            |  |             |
|                  |  |             |