



| グレーチング | | | 受 枠 | | 荷重条件 | |
|--------------|-----------------|-------------|------|---------|------|-----|
| 型 式 | メインバー 高さ (h) | クロスバー 材料 | 型 式 | 寸法 H | 横断 | 側溝 |
| S4FX040-1510 | 15 | FB3×10 | B-15 | 18 | 人 | T2 |
| S4FX040-2010 | 20 | FB3×10 | B-20 | 23 | T2 | T2 |
| S4FX040-2510 | 25 | FB3×15 | B-25 | 28 | T2 | T6 |
| S4FX040-3210 | 32 | FB3×15 | B-32 | 35 | T14 | T20 |
| S4FX040-3810 | 38 | FB3×20 | B-38 | 41 | T20 | T20 |
| S4FX040-4510 | 45 | FB3×20 | B-45 | 48 | T20 | T20 |
| S4FX040-5010 | 50 | FB3×20 | B-50 | 53 | T20 | T20 |

記事

- 溝幅 : 350用 (10mmピッチ)
- タイプ : FB4t, NSタイプ
- 材質 : SUS304

| | | |
|------------------|--|-------------------|
| APPROVED BY | | WORK NO. |
| JUDGED BY | | |
| ENG' R IN CHARGE | | DRAWING NO. |
| CHECKED BY | | |
| DRAWN BY | | |
| DATE DRAWN | | |
| SCALE | | DAIKURE CO., LTD. |